

Purpose:

The dispatch communication console «PSS» provides an official traffic to the command posts' officials, as well as to the engineering personnel of various-purpose units, both fixed and mobile.

The dispatch communication console provides:

- connection of 8 (eight) local battery lines;
- connection of 1 (one) automatic telephone exchange line;
- negotiating via any of the lines using a monophone;
- negotiating via any of the lines using a loudspeaker equipment;
- opportunity of simultaneous operation of two operators (the first operator uses the monophone, the second operator uses the loudspeaker equipment);
- opportunity of a simultaneous talk (selector communication) with several subscribers either in loudspeaker communication mode or via the monophone;
- opportunity of all local battery lines' monitoring on the internal speaker (may be used for the operation with user terminals without a magneto call).



Construction:

Structurally, the dispatch communication console may be wall-mounted and desktop-mounted.

Power supply:

Power supply of the dispatch communication console «PSS» is realized from 220V AC mains via adapters or 19 – 72 VDC power supply.

Operational conditions:

Resilience, durability, resistance of the dispatch communication console «PSS» to external influencing factors meet the requirements of the operating group 1.7 GOST standard 20.39.304-76 of the climatic version «humid microthermal climate».

Certificate:

The Certificate of Production of domestic manufacture № 644.1/6473-1, issued by the Chamber of Commerce and Industry of the Republic of Belarus.

